MATERIAL SAFETY DATA SHEET

EAGLE ABRASIVES, INC.

4025 Steve Reynolds Blvd.
Norcross, GA 30093

DATE REVISED: August 1, 2003

I. GENERAL INFORMATION

PRODUCT: Super-Tack Mini Yellow-Film Discs
PART# : 730-0800; 730-1500

CHEMICAL NAME & SYNONYMS:
Grain, Backing, Binding System, Anti-clog system, Nylon pile
CHEMICAL FAMILY:
N/A
PROPER DOT SHIPPING NAME:
N/A

TRADE NAME & SYNONYMS:
Super-Tack Mini Yellow-Film Discs
FORMULA:
N/A
DOT HAZARD CLASSIFICATION:
Not Restricted
MANUFACTURER'S PHONE # : 770-279-8111
CHEMTRAC PHONE # : Not Used

II. INGREDIENTS

CHEMICAL NAME	%	COMMON NAME	REG.	CAS. #	THRESHOLD LIMIT VALUE (UNITS)	CARCINOGEN
Grain	30	Aluminium Oxide	N	1344-28-1	15mg/m^3 OSHA, 10mg/m^3 ACGIH	N
Backing	25	Polyester Film	N			N
Binding System	28	Mixture	N			N
Anti-clog	10	Stearic Acid	N	1592-23-0		N
Velour	7	Nylon Pile	N			N

III. PHYSICAL DATA

BOILING POINT: (F) N/A	**SPECIFIC GRAVITY: (H_20 = 1)** N/A
VAPOR PRESSURE: (mm Hg.) N/A	**PERCENT VOLATILE BY VOLUME: (%)** N/A
VAPOR DENSITY: (Air = 1) N/A	**EVAPORATION RATE: (= 1)** N/A
SOLUBILITY IN WATER: N/A	**ph:** N/A
APPEARANCE & ODOR: Film coated with abrasive materials.	

IV. FIRE & EXPLOSION HAZARD DATA

FLASH POINT (TEST METHOD): N/A
AUTO IGNITION TEMPERATURE: N/A
LEL: N/A
UEL: N/A
FLAMMABLE LIMITS: N/A
EXTINGUISHING MEDIA: N/A
SPECIAL FIRE FIGHTING PROCEDURES: Use respiratory protection.
UNUSUAL FIRE & EXPLOSION HAZARDS: Backing & resin will burn or decompose.

V. HEALTH HAZARD DATA

PRODUCT: Super-Tack Mini yellow-Film Discs
PART# : 730-0800; 730-1500

Threshold Value:
N/A

OSHA Threshold Limit Value:
N/A

ACGIH Threshold Limit Value:
N/A

Carcinogen - NTP Program:
N/A

Carcinogen -IARC Program:
N/A

SYMPTOMS OF EXPOSURE:
Coughing, shortness of breath, chronic dust may effect breathing capacity.
Not absorbed trough skin but may cause abrasion, eye irritation.

OTHER POTENTIAL HEALTH RISK:
During use on some materials, elevated sound levels may affect hearing.

Medical Conditions Aggravated by Exposure: N/A

Primary Routes of Entry: Inhalation, Ingestion, Skin, Eye

EMERGENCY FIRST AID:
INHALATION: Remove to fresh air, apply artificial respiration as needed. Obtain first aid or medical assistance.
INGESTION: Obtain first aid or medical assistance if needed.
SKIN: Obtain first aid or medical assistance if needed.
EYE: Wash with large amounts of water obtain first aid or medical assistance if needed.

VI. REACTIVITY DATA

STABILITY: Stable

CONDITIONS TO AVOID: N/A

INCOMPATIBILITY: N/A

MATERIALS TO AVOID: N/A

HAZARDOUS POLYMERIZATION: Will not occur.

CONDITIONS TO AVOID: N/A

HAZARDOUS DECOMPOSITION PRODUCTS: In use dust and decomposing resin system fumes are generated.

VII. ENVIRONMENTAL PROTECTION PROCEDURE

SPILL RESPONSE: Normal clean up procedure.

WASTE DISPOSAL METHOD: Standard landfill methods consistant with applicable federal, state & local laws.

VIII. SPECIAL PROTECTION INFORMATION

EYE PROTECTION: Recommended

SKIN PROTECTION: Gloves if desired.

RESPIRATORY PROTECTION:
As needed, approved dust respirator

VENTILATION RECOMMENDED: LOCAL: recommended
MECHANICAL: recommended
OTHER: NAIF

OTHER PROTECTION:
Measure to be taken during repair and maintenance of contaminated equipment that has been contact with this material: SEE Section VI, VII, VIII.

IX. SPECIAL PRECAUTIONS

HYGENIC PRACTICES IN HANDLING & STORAGE: N/A.

PRECAUTIONS FOR REPAIR & MAINTENANCE OF CONTAMINATED EQUIPMENT: N/A

OTHER PRECAUTIONS: N/A